CITY OF PITTSBURGH

DEPARTMENT OF PUBLIC WORKS - BUREAU OF ENGINEERING DETECTABLE WARNING TRUNCATED DOME ACCESS RAMP - DETAILS

Approved: 12-14-07 STREETS DIVISION

Approved: 12/14/61 ASSISTANT DIRECTOR Approved: 12/14/01


"CAUTION"

NO CITY MONUMENTS ARE TO BE REMOVED OR DESTROYED DURING CONSTRUCTION.

COLOR OF DWTD PAD TO CONTRAST WITH ADJACENT SURFACE BY AT LEAST 70%. STD. IS BLACK FULL DEPTH. USE ONLY A CONCRETE PROTECTIVE COATING AND SEALER THAT IS CLEAR WHEN CURED.

USE EPOXY COATED 4 GA. 6X6 WIRE MESH IN DWTD PAD AND ACCESS RAMP.

USE CITY CLASS PP CONCRETE IN BOTH ACCESS RAMP AND DWTD PAD. **DWTD PAD SHALL BE COLORED FULL DEPTH.**



➤ C

SECTION C - C DETECTABLE WARNING TRUNCATED DOME (DWTD) **DETAIL**



POLYURETHANE, NON-SAG, CAULK 3/8" COMPRESSIBLE FOAM BACKER ROD

1/4" EXP. JT. (TYP. ALL **AROUND PRECAST PADS)**

MATERIALS FOR DWTD PADS ARE PRECAST CONCRETE. CAST-PLACE CONCRETE, CAST IRON, AND BRICKS. AS DIRECTED.

